


Walk in Temperature (& Humidity) Chamber




Mobile phone scan
More product information

Energy Conservation



Remote network system



Circuit System



• Specifications

Model		SMC-080-CC-WT	SMC-120-CC-WT	SMC-160-CC-WT	SMC-250-CC-WT	SMC-340-CC-WT	SMC-400-CC-WT
Temperature	Temperature control range	-65℃~80℃(+15℃) (A:0℃~80℃;B: -20℃~80℃; C: -40℃~80℃;D:-65℃~80℃)					
	Temperature fluctuation	±0.5℃					
	Cooling rate	80.0℃~-65.0℃ Within 110 mins 1.0~2.0℃/min					
	Heating rate	-65.0℃~80.0℃ Within 70 mins 2.0~5.0℃/min					
Humidity	Temperature uniformity	±2.0℃ (-40.0℃~80.0℃) ±2.5℃ (-40.0℃~-65.0℃)					
	Humidity control range	20.0%RH~95.0%RH					
	Humidity fluctuation	±1.5% RH					
Material / components	Humidity uniformity	±3.0%RH					
	Internal material	Stainless steel(SUS304)					
	External material	Cold rolled steel sheet / powder spraying					
	Heat insulating material	100mm thickness polyurethane plate+10mm thickness mineral wool					
	Fan	SANWOOD® Centrifugal blower					
	Compressor	Semi-closed Germany Bock, Germany Bitzer					
	Condenser	Water-cooled					
	Refrigerant	R404A、R23、R508					
	Evaporator	Fin - and - Tube Heat Exchanger					
Size	Heater	Nickel chromium alloy heating wire					
	Humidifier	Steam humidifier					
	Interior size(mm)	1970*2100*1970	3020*2100*1970	4070*2100*1970	3020*2100*4070	4070*2100*4070	5120*2100*4070
Operating ambient temperature	Outer size(mm)	2170*2350*3500	3220*2350*3500	4270*2350*3500	4650*2350*4270	5720*2350*4270	5320*2350*6150
	Volume (m³)	8.0m³	12.0m³	16.0m³	25.0m³	34.0m³	40.0m³
Power supply	+5 ~ 35℃						
Controller	Standard: South Korea TEMI-1500 Optional: South Korea TEMI-2500, South Korea TEMI-2700						

Sanwood (HK) Industrial Corporation.,limited
Guangdong Sanwood Technology Corporation.,limited

ADD: No.88, Songchang Road, Songbotang , Changping, Dongguan, Guangdong
TEL: +86+769-81182799
FAX: +86+769-82987199
E-mail: info@sanwood.cc
www.sanwood.cc
www.climatic-chambers.com



Mobile phone scan
can visit our official website